


Cam. 425 - 455

| | | | | | |
|---|--------------------|----------------|---------------------------|-------------------------|--------------------------|
| Conforme alla Direttiva 2002/95/EC (RoHS) Compliant with Directive 2002/95/EC (RoHS) | | | | | |
| MODELLO MODEL | TAMAYA 04 NW FLASH | | DISEGNO N. DRAWING NO. | DW02020 | |
| PARTICOLARE DETAIL | DISEGNO INGOMBRO | | REL LEVEL REL LEVEL | DATA DATE | |
| SUP. BAGNATA WET SURFACE | MASSA MASS | SPESS. TCKN | REVISIONE REVISION | ITERAZIONE ITERATION | DISEGNATO DA DRAWN BY |
| | | | A | 2 | CIMARRA |



www.elica.com



| | | | | | | | | | | | | | | | | | | | | | | | | | | |
|--|------------------------------------|------------------------------------|----------|-------|----------|-------|----------|-------|----------|-------|----------|-------|---------|-------|--------|-------|--------|-------|--------|-------|--------|-------|-------|-------|-----|-------|
| ELABORATO CON SISTEMA CAD DESIGNED BY CAD SYSTEM | | | | | | | | | | | | | | | | | | | | | | | | | | |
| QUOTA PRIMARIA XX PRIMARY DIMENSION | | | | | | | | | | | | | | | | | | | | | | | | | | |
| ANGOLI Angles ±0°30' | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <table border="1"> <tr> <td>>500</td> <td>±0.75</td> </tr> <tr> <td>>400-500</td> <td>±0.65</td> </tr> <tr> <td>>315-400</td> <td>±0.60</td> </tr> <tr> <td>>250-315</td> <td>±0.55</td> </tr> <tr> <td>>180-250</td> <td>±0.50</td> </tr> <tr> <td>>120-180</td> <td>±0.45</td> </tr> <tr> <td>>80-120</td> <td>±0.40</td> </tr> <tr> <td>>50-80</td> <td>±0.35</td> </tr> <tr> <td>>30-50</td> <td>±0.30</td> </tr> <tr> <td>>18-30</td> <td>±0.25</td> </tr> <tr> <td>>10-18</td> <td>±0.20</td> </tr> <tr> <td>>5-10</td> <td>±0.15</td> </tr> <tr> <td>0-5</td> <td>±0.10</td> </tr> </table> | >500 | ±0.75 | >400-500 | ±0.65 | >315-400 | ±0.60 | >250-315 | ±0.55 | >180-250 | ±0.50 | >120-180 | ±0.45 | >80-120 | ±0.40 | >50-80 | ±0.35 | >30-50 | ±0.30 | >18-30 | ±0.25 | >10-18 | ±0.20 | >5-10 | ±0.15 | 0-5 | ±0.10 |
| >500 | ±0.75 | | | | | | | | | | | | | | | | | | | | | | | | | |
| >400-500 | ±0.65 | | | | | | | | | | | | | | | | | | | | | | | | | |
| >315-400 | ±0.60 | | | | | | | | | | | | | | | | | | | | | | | | | |
| >250-315 | ±0.55 | | | | | | | | | | | | | | | | | | | | | | | | | |
| >180-250 | ±0.50 | | | | | | | | | | | | | | | | | | | | | | | | | |
| >120-180 | ±0.45 | | | | | | | | | | | | | | | | | | | | | | | | | |
| >80-120 | ±0.40 | | | | | | | | | | | | | | | | | | | | | | | | | |
| >50-80 | ±0.35 | | | | | | | | | | | | | | | | | | | | | | | | | |
| >30-50 | ±0.30 | | | | | | | | | | | | | | | | | | | | | | | | | |
| >18-30 | ±0.25 | | | | | | | | | | | | | | | | | | | | | | | | | |
| >10-18 | ±0.20 | | | | | | | | | | | | | | | | | | | | | | | | | |
| >5-10 | ±0.15 | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0-5 | ±0.10 | | | | | | | | | | | | | | | | | | | | | | | | | |
| <table border="1"> <tr> <td>QUOTE SENZA TOLLERANZA</td> <td>TOLLERANCE UNLESS OTHERWISE STATED</td> </tr> </table> | QUOTE SENZA TOLLERANZA | TOLLERANCE UNLESS OTHERWISE STATED | | | | | | | | | | | | | | | | | | | | | | | | |
| QUOTE SENZA TOLLERANZA | TOLLERANCE UNLESS OTHERWISE STATED | | | | | | | | | | | | | | | | | | | | | | | | | |
| LUNGH. E DIAM. LENGHT AND DIAM. | | | | | | | | | | | | | | | | | | | | | | | | | | |